## **IN THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing Of Claims:**

Please amend the claims as follows:

- 1. (Canceled)
- 2. (Canceled)
- 3. (Canceled)
- 4. (Canceled)
- 5. (Currently Amended) A cable, comprising:
- a central strength member;

a buffer tube stranded around the central strength member, the buffer tube loosely housing at least one optical fiber placed in the buffer tube precedent to an installation of the cable;

a first conduit configured to receive at least one first blown optical fiber

subsequent to the installation of the cable and positioned external to the central strength

member;

an outer jacket positioned at the periphery of the cable; and

an inner jacket positioned inside the outer jacket and surrounding at least the central strength member and the buffer tube, The cable of claim 4, wherein the first conduit is positioned outside the inner jacket.

- 6. (Original) The cable of claim 5, wherein the first conduit and the inner jacket have substantially identical inner diameters.
- 7. (Original) The cable of claim 5, further comprising a second conduit configured to receive at least one second blown optical fiber and positioned outside the inner jacket.
  - 8. (Canceled)
  - 9. (Currently Amended) <u>A cable, comprising:</u>

a central strength member;

a buffer tube stranded around the central strength member, the buffer tube loosely housing at least one optical fiber placed in the buffer tube precedent to an installation of the cable;

a first conduit configured to receive at least one first blown optical fiber
subsequent to the installation of the cable and positioned external to the central strength
member;

an outer jacket positioned at the periphery of the cable;

an inner jacket positioned inside the outer jacket and surrounding at least the central strength member and the buffer tube and wherein the first conduit is positioned inside the inner jacket; and

The cable of claim 8, further comprising a second conduit configured to receive at least one second blown optical fiber and positioned outside the inner jacket.

- 10. (Canceled)
- 11. (Canceled)
- 12. (Currently Amended) A cable, comprising:
- a central strength member;

a buffer tube stranded around the central strength member, the buffer tube loosely housing at least one optical fiber placed in the buffer tube precedent to an installation of the cable;

a first conduit configured to receive at least one first blown optical fiber subsequent to the installation of the cable and positioned external to the central strength member;

an outer jacket positioned at the periphery of the cable;

a first water blocking layer surrounding the central strength member; and

The cable of claim 11, further comprising an outer strength member located

substantially parallel to the central strength member and inside the outer jacket.

13. (Original) The cable of claim 12, further comprising a second water blocking layer located between the outer strength member and the central strength member.

- 14. (Canceled)
- 15. (Canceled)
- 16. (Canceled)
- 17. (Canceled)
- 18. (Currently Amended) A cable, comprising:

a central strength member, wherein the central strength member includes a bore configured to receive at least one central blown optical fiber;

a conductor of electrical energy stranded around the central strength member;

a first conduit configured to receive at least one first blown optical fiber

subsequent to an installation of the cable and positioned external to the central strength member;

an outer jacket positioned at the periphery of the cable; and

The cable of claim 15, wherein the first conduit is positioned outside [[the]] an inner jacket.

19. (Canceled)

20. (Original) The cable of claim 18, further comprising a second conduit configured to receive at least one second blown optical fiber and positioned outside the inner jacket.

21. (Canceled)